

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **Interflon Slide Wax Dry (Aerosol)**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Scope lubricant

#### 1.3 Details of the supplier of the safety data sheet

Interflon BV  
Belder 47  
4704 RK Roosendaal  
Netherlands

Telephone: +31 (0)165 553911  
e-mail: Service@Interflon.com  
Website: www.Interflon.com

e-mail (competent person) msds.uk@interflon.com

#### 1.4 Emergency telephone number

Poison centre					
Country	Name	Postal code/ city	Telephone	Telefax	Opening hours
United Kingdom	UK National Poison Centre		UK National Poisons Emergency number: +44 870 600 6266		Mon - Fri 12:00 AM - 11:00 PM

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

#### 2.2 Label elements

Labelling

- Signal word. danger

## Interflon Slide Wax Dry (Aerosol)

**Version number:**

3.8

Replaces version: (2)

08.01.2021

08.01.2021:

**- Pictograms**

GHS02, GHS07



**- Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

**- Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P312 Call a POISON CENTRE/doctor if you feel unwell.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container to industrial combustion plant.

**- Supplemental hazard information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Additional labelling according to Directive 75/324/EEC relating to aerosol dispensers**

Extremely flammable. Pressurized container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**- Hazardous ingredients for labelling**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics, Isopropanol

### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Product description

Mixture of waxes, solvents, additives and Micpol

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
butane	CAS No 106-97-8  EC No 203-448-7  Index No 601-004-00-0	25 – < 50	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) K(b)

## Interflon Slide Wax Dry (Aerosol)

Version number:

3.8

Replaces version: (2)

08.01.2021

08.01.2021:

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
Propane	CAS No 74-98-6  EC No 200-827-9  Index No 601-003-00-5	10 – < 25	Flam. Gas 1 / H220 Press. Gas L / H280	
isobutane	CAS No 75-28-5  EC No 200-857-2  Index No 601-004-00-0	10 – < 25	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) GHS-HC U
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	EC No 920-750-0	5 – < 10	Flam. Liq. 2 / H225 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC No 927-241-2	5 – < 10	Flam. Liq. 3 / H226 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412	
Isopropanol	CAS No 67-63-0  EC No 200-661-7  Index No 603-117-00-0	5 – < 10	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	GHS-HC
Ethanol	CAS No 64-17-5  EC No 200-578-6	5 – < 10	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319	IARC: 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS No 64742-48-9  EC No 918-481-9  Index No 649-327-00-6	1 – < 5	Asp. Tox. 1 / H304	

### Notes

C(a): Mixture of isomers

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)

K(b): The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-) P210-P403 should apply

U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water mist, Fire extinguishing powder

##### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

##### Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Remove persons to safety.

##### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

## Interflon Slide Wax Dry (Aerosol)

**Version number:**

3.8

Replaces version: (2)

08.01.2021

08.01.2021:

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.

### 7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
GB	butane	106-97-8	WEL	600	1,450	750	1,810				EH40/2005
GB	ethanol	64-17-5	WEL	1,000	1,920						EH40/2005
GB	propan-2-ol	67-63-0	WEL	400	999	500	1,250				EH40/2005

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

### Notation

Ceiling-C  
STEL ceiling value is a limit value above which exposure should not occur  
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours  
time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		DNEL	2,035 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		DNEL	773 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		DNEL	871 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		DNEL	77 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Isopropanol	67-63-0	DNEL	500 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Isopropanol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Isopropanol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Isopropanol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Isopropanol	67-63-0	PNEC	2,251 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Isopropanol	67-63-0	PNEC	552 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Isopropanol	67-63-0	PNEC	552 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Isopropanol	67-63-0	PNEC	28 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### General safety precautions

Use only in well-ventilated areas.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
Keep away from food, drink and animal feedingstuffs. Do not breathe gas/vapour/spray. Wash hands after use.

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Use safety goggle with side protection.

#### Skin protection

##### - Hand protection

Wear suitable gloves. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.

##### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid, gaseous (spray aerosol)
Colour	white
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	-12 °C
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	0.9 vol% - 12 vol%
Flash point	-13 °C
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not relevant
Solubility(ies)	not determined

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

### Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	3,000 hPa at 20 °C
-----------------	--------------------

### Density and/or relative density

Density	0.62 g/cm <sup>3</sup>
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

## 9.2 Other information

Information with regard to physical hazard classes

Aerosols

- Components (flammable)	93.48 %
Other safety characteristics	there is no additional information

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains re-active substance(s). Risk of ignition.

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

### 10.5 Incompatible materials

Oxidisers

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

**Interflon Slide Wax Dry (Aerosol)**

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

**Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to GHS****Acute toxicity**

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9	inhalation: vapour	>9.3 mg/l/4h

**Skin corrosion/irritation**

Shall not be classified as corrosive/irritant to skin.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

Shall not be classified as a respiratory or skin sensitiser.

**Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

**Carcinogenicity**

Shall not be classified as carcinogenic.

**Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

**Specific target organ toxicity - single exposure**

May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

**Other information**

Repeated exposure may cause skin dryness or cracking.

**11.2 Information on other hazards**

There is no additional information.

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

### SECTION 12: Ecological information

#### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		EL50	1.6 mg/l	aquatic invertebrates	21 d
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		EC50	0.23 mg/l	aquatic invertebrates	21 d
Ethanol	64-17-5	LC50	1,806 mg/l	aquatic invertebrates	10 d
Ethanol	64-17-5	ErC50	675 mg/l	algae	4 d
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9	LL50	>100 mg/l	fish	3 h

#### 12.2 Persistence and degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		oxygen depletion	83 %	16 d		ECHA
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		oxygen depletion	8 %	3 d		ECHA
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		carbon dioxide generation	0 %	3 d		ECHA
Isopropanol	67-63-0	oxygen depletion	53 %	5 d		ECHA
Ethanol	64-17-5	oxygen depletion	69 %	5 d		ECHA
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9	carbon dioxide generation	0 %	3 d		ECHA

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

Degradability of components of the mixture						
Name of sub- stance	CAS No	Process	Degradation rate	Time	Method	Source
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9	oxygen depletion	31.3 %	28 d		ECHA

### 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
Propane	74-98-6		1.09 (pH value: 7, 20 °C)	
isobutane	75-28-5		1.09 (pH value: 7, 20 °C)	
Ethanol	64-17-5		-0.77	0.6211
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9	≥44.6 – ≤5,362	≥3.17 – ≤7.22	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

None of the ingredients are listed.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

List of wastes

- Product

- 15 01 04 metallic packaging
- 16 05 04\* gases in pressure containers (including halons) containing hazardous substances
- 20 01 13\* solvents

## Interflon Slide Wax Dry (Aerosol)

**Version number:**

3.8

Replaces version: (2)

08.01.2021

08.01.2021:

### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR/RID	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

#### 14.2 UN proper shipping name

ADR/RID	AEROSOLS
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

#### 14.3 Transport hazard class(es)

ADR/RID	2 (2.1)
IMDG-Code	2.1
ICAO-TI	2.1

#### 14.4 Packing group

not assigned

#### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

#### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

#### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### Information for each of the UN Model Regulations

#### Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information

Classification code	5F
Danger label(s)	2.1



Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D

#### Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) - Additional information

Classification code	5F
---------------------	----

## Interflon Slide Wax Dry (Aerosol)

**Version number:**

3.8

Replaces version: (2)

08.01.2021

08.01.2021:

Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ) E0

Limited quantities (LQ) 1 L

Transport category (TC) 2

Hazard identification No 23

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant -

Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0

Limited quantities (LQ) 1 L

EmS F-D, S-U

Stowage category -

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 2.1



Special provisions (SP) A145, A167

Excepted quantities (EQ) E0

Limited quantities (LQ) 30 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

#### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P3a	flammable aerosols (containing Flam. Gas or Flam. Liq.)	150 500	46)

#### Notation

46) 'flammable' aerosols category 1 or 2, containing flammable gases category 1 or 2 or flammable liquids category 1  
Note: qualifying quantity = net

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

### Industrial Emissions Directive (IED)

VOC content	96.57 %
-------------	---------

### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

### National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
EU	REACH Reg.	all ingredients are listed or exempt from listing
US	TSCA	not all ingredients are listed

#### Legend

DSL Domestic Substances List (DSL)  
REACH Reg. REACH registered substances  
TSCA Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
1.1	Registration number (REACH): not relevant (mixture)		yes
1.1	Unique formula identifier UFI: 7910-50SW-A00F-M9J4		yes
1.3	e-mail (competent person): Service@interflon.com (Service lab)	e-mail (competent person): msds.uk@interflon.com	yes
2.1	Classification according to Regulation (EC) No 1272/2008 (CLP)	Classification acc. to GHS	yes
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.2	Labelling according to Regulation (EC) No 1272/ 2008 (CLP)	Labelling	yes
2.3	Other hazards: of no significance	Other hazards: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes
3.2		Hazardous ingredients: change in the listing (table)	yes

## Interflon Slide Wax Dry (Aerosol)

Version number:

3.8

Replaces version: (2)

08.01.2021

08.01.2021:

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
4.2	Most important symptoms and effects, both acute and delayed: Narcotic effects.	Most important symptoms and effects, both acute and delayed: Symptoms and effects are not known to date.	yes
5.1	Suitable extinguishing media: Water spray, BC-powder	Suitable extinguishing media: Water mist, Fire extinguishing powder	yes
5.3	Advice for firefighters: In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.	Advice for firefighters: In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.	yes
7.1	Advice on general occupational hygiene: Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.	Advice on general occupational hygiene: Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.	yes
7.2	- Flammability hazards: Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	- Flammability hazards: Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.2	General safety precautions: Use only in well-ventilated areas. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes. Do not eat, drink and smoke in work areas.	General safety precautions: Use only in well-ventilated areas. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes. Keep away from food, drink and animal feeding-stuffs. Do not breathe gas/vapour/spray. Wash hands after use.	yes
8.2	Eye/face protection: Wear eye/face protection. Use safety goggle with side protection.	Eye/face protection: Use safety goggle with side protection.	yes
8.2	Respiratory protection: Not required.	Respiratory protection: Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).	yes
9.1	Physical state: liquid, solid, gaseous (spray aerosol)	Physical state: liquid, gaseous (spray aerosol)	yes
9.1	Colour: cloudy	Colour: white	yes
9.1		Relative vapour density: information on this property is not available	yes
9.1	Particle characteristics: no data available	Particle characteristics: not relevant (aerosol)	yes
9.2	Other safety characteristics	Other safety characteristics: there is no additional information	yes

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
9.2	Propellant content: 67 %		yes
11.1	Information on hazard classes as defined in Regulation (EC) No 1272/2008	Information on toxicological effects	yes
11.1	Classification according to GHS (1272/2008/EC, CLP)	Classification acc. to GHS	yes
11.1		Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes
12.2		Degradability of components of the mixture: change in the listing (table)	yes
12.3		Bioaccumulative potential of components of the mixture: change in the listing (table)	yes
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes
14.1	ADR/RID/ADN	ADR/RID	yes
14.2	ADR/RID/ADN	ADR/RID	yes
14.3	ADR/RID/ADN	ADR/RID	yes
14.7	Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information	Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information	yes
14.7		Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) - Additional information	yes
14.7		Classification code: 5F	yes
14.7		Danger label(s): 2.1	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Special provisions (SP): 190, 327, 344, 625	yes
14.7		Excepted quantities (EQ): E0	yes
14.7		Limited quantities (LQ): 1 L	yes
14.7		Transport category (TC): 2	yes
14.7		Hazard identification No: 23	yes
15.1	Restrictions according to REACH, Annex XVII		yes

## Interflon Slide Wax Dry (Aerosol)

Version number:

3.8

Replaces version: (2)

08.01.2021

08.01.2021:

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1		Dangerous substances with restrictions (REACH, Annex XVII): change in the listing (table)	yes
15.1	List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list: none of the ingredients are listed		yes
15.1	Deco-Paint Directive (2004/42/EC)		yes
15.1	VOC content: 96.57 %		yes
15.1	Directive on industrial emissions (VOCs, 2010/75/EU)	Industrial Emissions Directive (IED)	yes
15.1	Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II	Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)	yes
15.1	Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)	Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)	yes
15.1		Regulation on persistent organic pollutants (POP): None of the ingredients are listed.	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16	Key literature references and sources for data: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU. Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	Key literature references and sources for data: Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	yes
16	List of relevant phrases (code and full text as stated in chapter 2 and 3)	List of relevant phrases (code and full text as stated in section 2 and 3)	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand

## Interflon Slide Wax Dry (Aerosol)

Version number:

3.8

Replaces version: (2)

08.01.2021

08.01.2021:

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer

## Interflon Slide Wax Dry (Aerosol)

**Version number:**  
3.8  
Replaces version: (2)

08.01.2021

08.01.2021:

Abbr.	Descriptions of used abbreviations
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Press. Gas	Gas under pressure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.  
Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Interflon Slide Wax Dry (Aerosol)****Version number:**

3.8

08.01.2021

08.01.2021:

Replaces version: (2)

---

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.