

Technical Data Sheet

Interflon Eco Degreaser

Human and environmentally friendly Degreaser and Cleaner

Industrial strength "ready to use" degreaser with F-Active Technology that degrades organic matter ensuring strong cleaning properties. Allows effective cleaning and degreasing of a wide range of surfaces quickly, easily and efficiently. Contains unique, active substances for quickly and effectively removing contamination, such as grease residue, used oil, hydrocarbons, graphite, ink, tar, polymers, polystyrene, glue, wax and bitumen. In addition Interflon Eco Degreaser also has been shown to have virucidal activity against enveloped viruses. The product has been tested according to NF EN14476:2013 + A2: 2019.

Interflon Eco Degreaser is listed by the NSF for use in the food industry as a general cleaner.

Applications

Daily cleaning and degreasing of surfaces such as stainless steel, plastic, marble, ceramic and textiles. Suitable for ultrasonic baths. Degreasing of glass surfaces, tools and surfaces with organic dirt, especially fatty contamination in the food industry. Suitable for cleaning programs under HACCP systems.

Advantages

- ⦿ Ready to use
- ⦿ Does not attack paint
- ⦿ Non-flammable
- ⦿ Exempt from hazardous labeling
- ⦿ No storage or transportation restrictions
- ⦿ Sustainable - European Eco-Labe certificate (NL/20/025)

Instructions for use

Metal surfaces and worktops: apply directly and allow it to work for several seconds (20 - 40 seconds depending on contamination). A longer contact time will result in a better cleaning action. Remove with a clean, damp cloth then wipe with a dry cloth. On glass and ceramic: saturate the area to be cleaned and wipe with a dry cloth. For food industry utensils and surfaces: apply the product, allow it to work, and then rinse off.

Do not apply on painted surfaces or polycarbonate without a prior test. Do not mix different cleaners. Avoid inhaling sprayed product. Using the required quantity saves costs and minimizes environmental impacts.

Property	Result	Method
Composition	Mixture of surface-active substances, enzymes and water	-
Colour	Blue	-
Odour	Characteristic	-
Density 20°C	0.99 g/cm ³	-
Highest application temperature	80°C	-
pH 100 20°C	10.5 - 11.5	-
Shelf life*	3 years	-
Evaporation speed	Not determined	-
Vapour pressure 20°C	23 hPa	-
NSF registration number	153150	
NSF	A1	
Halal	Yes	
Kosher	Yes	

* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.