EG-A-LOOSE PENETRANT LUBRICANT

GENERAL DESCRIPTION

MEG-A-LOOSE is a mixture of active rust dissolvers in conjunction with a unique blend of lubricants making it far more effective than conventional penetrating products. Provides superior lubrication during dissembly to prevent seizing.

AREAS OF APPLICATION

Penetrating to free frozen nuts, bolts, screws, lags, fasteners and working parts. Providing pressure and wear resistant lubrication of tightly threaded fittings, parts, locks, hinges, linkages and tools. Flushes out dirt and old contaminated lubricants while at the same time providing increased penetration to free parts and at the same time deeply deposit a micronic lubricating blend of molybdenum and additional quality lubricants to lubricate where most needed.

SPECIAL FEATURES

Highly Effective - strong rust dissolvers free blocked parts quickly. Accelerated penetration through rust and dirt to free working mechanisms quickly.

Repels Moisture - drives out moisture and quards against the further effects of water and corrosion.

Cleans and Protects - cleans and flushes all mechanical surfaces while providing a residual protective coating.

Superior Lubrication - provides superior lubrication during disassembly as well as in continued use. Contains a unique superior lubricant blend, including molybdenum, to greatly extend lubricating properties. Eliminates squeaks and squeals.

Safe To Use - does not adversely effect rubber. Excellent for all types of metal or metal combinations, even sensitive applications such as steel/aluminum joints. Contains no silicone or chlorinated solvents.

USE DIRECTIONS

Saturate frozen or stiff parts and allow to stand for a few minutes before attempting to break free. Loosen parts carefully. A wire brush should be used prior to spraying wherever heavily encrusted rust, corrosion or scale is encountered. Respray parts before and after reassembly for improved working conditions as well as easier future disassembly.

Physical properties - Aerosol

MEG-A-LOOSE consists of a unique blend of specially selected quality lubricants and penetrants.

Туре	Aerosol Lubricant/Penetrant
Appearance	Green/Grey Liquid
Odour	Characteristic Solvent
Viscosity	Water Thin
Flammability	Extremely Flammable
Specific Gravity	0.80
Solubility in Water	Negligible
Toxicity (concentrate)	Eye/Skin Irritant
Avoid pr	olonged breathing of vapours

FOR USE IN INDUSTRIAL. INSTITUTIONAL. MARINE AND COMMERCIAL **ENVIRONMENTS**

PACKAGING

Aerosol Case (12 x 376g Cans)





