Profi-Series

ONE-PIECE ROTO-MOULD CHASSIS
practically indestructible
plastic housing

CONVENIENT INTEGRATED HOSE REEL (TST)
space-saving storage of the high-pressure
hose-with foldable crank

WATER TANK
helps prevent damage to the
device in case of water shortage

STAINLESS STEEL PRESSURE GAUGE
easy reading of the working pressure

ACCESSORY STORAGE
neat storage for high pressure
gun and lances

OFF-ROAD CAPABILITY AND STABILITY
robust chassis for easy transport and
high stability

606000 Profi 160 TST

► **ACCESSORIES** | starting on page 22

EQUIPMENT

- Quick release plug-in system D12
- Total-Stop system
- Pressure regulation
- Cleaning Agent Intake
- Direct suction: Suction height 2.5 m
- Detachable water tank: Volume 1.3 liters

VARIANT - NON-MARKING

NOM conversion kit	Ord.no.	**42260**

For further information on NON-Marking please refer to page 74

MODEL		Profi 160 TST	Profi 195 TST	Profi 175 TST
Ord.no. TST incl. hose drum		**606000**	**606010**	**606100**
TECHNICAL SPECIFICATIONS				
Operating pressure	bar | MPa	30-140 | 3-14	30-170 | 3-17	30-150 | 3-15
Water output	l/min | l/h	11 | 660	8 | 480	12 | 720
Admissible overpressure	bar | MPa	160 | 16	195 | 19.5	175 | 17.5
Motor speed	Rpm	1400	1400	1400
Connection	V | ~ | Hz | A	230 | 1 | 50 | 14.3	230 | 1 | 50 | 14.3	400 | 3 | 50 | 7.2
Power intake | Power output	kW	3.2 | 2.5	3.2 | 2.5	3.8 | 3.0
Power supply cable	m	5	5	5
Dimensions L x W x H	mm	355 | 375 | 980	355 | 375 | 980	355 | 375 | 980
Weight	kg	45	45	45
EQUIPMENT				
High-pressure hose	m | Ord.no.	15 (DN 6) | 43829	15 (DN 6) | 43829	15 (DN 6) | 43829
Trigger gun with safety catch	Model | Ord.no.	M2000 | 12481	M2000 | 12481	M2000 | 12481
Stainless steel lance with flat-jet nozzle	Nozzle | Ord.no.	● 042 | 12435-M20042	○ 03 | 12435-M2003	● 042 | 12435-M20042
Lance with Dirtkiller	Nozzle | Ord.no.	● 042 | 12438-042	○ 03 | 12438-03	● 042 | 12438-042